



- > 0 ... 630 bar (0 ... 9137 psi)
Port size: G1/4 or flange
- > Display of system pressure (unit bar, psi, mpa programmable)
- > Easy programming of switchpoints and extra functions

- > Economic solution for industrial applications
- > Electronic lock
- > Switching status indicated by LED
- > With digital and analogue output
- > UL-Approval



Technical features

Medium:

For neutral and aggressive, gaseous and liquid fluids

Pressure range:

0 ... 630 bar (0 ... 9137 psi)

Switching pressure difference:

Programmable

Switching point:

Adjustable between

0 ... 100% of full scale (FS)

Reset point:

Adjustable between 0 ... 100% of full scale (FS)

(smallest adjustable pressure switching difference between switching point and reset point $\geq 0,5\%$ of full scale (FS))

Display:

LCD 4 digits, illuminated, pressure unit programmable bar, psi, mpa (customer specific pressure unit available on request)

Mounting position:

Optional

Total accuracy:

$\pm 1,5\%$ of full scale (FS) - without temperature sensitivity

Linearity:

$\pm 0,2\% + 1$ Display step size

Shockproof:

30 g, xyz, DIN EN 60068-2-27

Vibrationproof:

3 g, 5 ... 500 Hz, xyz, DIN EN 60068-2-6

Degree of protection acc. to DIN 40050:

IP65 (with plug mounted)

Weight:

0,09 kg (0.19 lbs)

Temperature sensitivity:

Zero point: $\pm 0,4\%$ of final value (FS) pro 10° Kelvin
Range: $\pm 0,4\%$ of final value (FS) pro 10° Kelvin

Ambient/Media temperature:

Ambient:

-10 ... +60°C (14 ... +140°F)

Media:

-10 ... +80°C (14 ... +176°F)

Air supply must be dry enough to avoid ice formation at temperature below +2°C (+35°F)

Materials:

Housing:

Aluminium/Stainless steel

Sensor (fluid-affected parts):

Stainless steel 1.4571

(0 ... 250 bar),

Stainless steel 1.4542

(400 ... 630 bar)

FS = full scale

Electrical parameters

Electrical connection:

M12 x 1

Power supply:

UB = 10 ... 32 V d.c.

15 ... 32 V d.c. (analogue)

polarity safe

Permissible residual ripple:

10% (within UB)

Current consumption:

< 50 mA

Switching mode:

PNP, potential-bound open collector switching to + UB

Output signal:

Digital: UB minus 1.5 V

Analogue: 4 ... 20 mA

Contact rating:

I_{max} = 500 mA (short circuit proof)

Switching time:

< 10 ms

Signal delay:

On/off 0 ... 20 s

Service life:

Min. 100 million switching cycles

Switching logic:

NO/NC programmable

Operating mode:

Standard, hysteresis and window mode separately selectable for each output


Electromagnetic compatibility:

According to EN 61326-1


Technical data - Output signal 1 x PNP

Symbol	Port size	Switching pressure range (bar)	Switching pressure range (psi)	Over pressure *1 (bar)	Over pressure *1 (psi)	Output signal	Display step size (bar)	Display step size (psi)	Model *1)
	G 1/4	0 ... 10	0 ... 145	40	580	1 x PNP	0,050	0.725	0863112
	Flange	0 ... 10	0 ... 145	40	580	1 x PNP	0,050	0.725	0863116
	G 1/4	0 ... 40	0 ... 580	100	1450	1 x PNP	0,200	2.90	0863312 *2)
	Flange	0 ... 40	0 ... 580	100	1450	1 x PNP	0,200	2.90	0863316
	G 1/4	0 ... 100	0 ... 1450	200	2900	1 x PNP	0,500	7.25	0863412 *2)
	Flange	0 ... 100	0 ... 1450	200	2900	1 x PNP	0,500	7.25	0863416
	G 1/4	0 ... 160	0 ... 2320	300	4351	1 x PNP	0,500	7.25	0863512
	Flange	0 ... 160	0 ... 2320	300	4351	1 x PNP	0,500	7.25	0863516
	G 1/4	0 ... 250	0 ... 3625	500	7251	1 x PNP	1,000	14.50	0863612 *2)
	Flange	0 ... 250	0 ... 3625	500	7251	1 x PNP	1,000	14.50	0863616
	G 1/4	0 ... 400	0 ... 5801	750	10877	1 x PNP	2,000	29.00	0863712 *2)
	G 1/4	0 ... 630	0 ... 9137	1000	14503	1 x PNP	2,000	29.00	0863812

Technical data - Output signal 2 x PNP

Symbol	Port size	Switching pressure range (bar)	Switching pressure range (psi)	Over pressure *1 (bar)	Over pressure *1 (psi)	Output signal	Display step size (bar)	Display step size (psi)	Model *1)
	G 1/4	0 ... 10	0 ... 145	40	580	2 x PNP	0,050	0.725	0863122
	Flange	0 ... 10	0 ... 145	40	580	2 x PNP	0,050	0.725	0863126
	G 1/4	0 ... 40	0 ... 580	100	1450	2 x PNP	0,200	2.90	0863322
	Flange	0 ... 40	0 ... 580	100	1450	2 x PNP	0,200	2.90	0863326
	G 1/4	0 ... 100	0 ... 1450	200	2900	2 x PNP	0,500	7.25	0863422 *2)
	Flange	0 ... 100	0 ... 1450	200	2900	2 x PNP	0,500	7.25	0863426
	G 1/4	0 ... 160	0 ... 2320	300	4351	2 x PNP	0,500	7.25	0863522
	Flange	0 ... 160	0 ... 2320	300	4351	2 x PNP	0,500	7.25	0863526
	G 1/4	0 ... 250	0 ... 3625	500	7251	2 x PNP	1,000	14.50	0863622 *2)
	Flange	0 ... 250	0 ... 3625	500	7251	2 x PNP	1,000	14.50	0863626
	G 1/4	0 ... 400	0 ... 5801	750	10877	2 x PNP	2,000	29.00	0863722 *2)
	G 1/4	0 ... 630	0 ... 9137	1000	14503	2 x PNP	2,000	29.00	0863822

Technical data - Output signal 1 x PNP/1 x analogue 4 ... 20 mA

Symbol	Port size	Switching pressure range (bar)	Switching pressure range (psi)	Over pressure *1 (bar)	Over pressure *1 (psi)	Output signal	Display step size (bar)	Display step size (psi)	Model *1)
	G 1/4	0 ... 10	0 ... 145	40	580	1 x PNP / 4 ... 20 mA	0,050	0.725	0863142
	G 1/4	0 ... 40	0 ... 580	100	1450	1 x PNP / 4 ... 20 mA	0,200	2.90	0863342
	G 1/4	0 ... 100	0 ... 1450	200	2900	1 x PNP / 4 ... 20 mA	0,500	7.25	0863442 *2)
	G 1/4	0 ... 160	0 ... 2320	300	4351	1 x PNP / 4 ... 20 mA	0,500	7.25	0863542
	G 1/4	0 ... 250	0 ... 3625	500	7251	1 x PNP / 4 ... 20 mA	1,000	14.50	0863642 *2)
	G 1/4	0 ... 400	0 ... 5801	750	10877	1 x PNP / 4 ... 20 mA	2,000	29.00	0863742
	G 1/4	0 ... 630	0 ... 9137	1000	14503	1 x PNP / 4 ... 20 mA	2,000	29.00	0863842

*1) Short-term pressure peaks are not allowed to exceed this limit value during operation. Operative utilization of the limit value is not permitted.

The limit value corresponds to the maximum testing pressure

*2) Preference type

Option selector

0863★★★

Pressure range (bar)	Substitute	Output signal	Substitute
0 ... 10	1	G 1/4	2
0 ... 40	3	Flange	6
0 ... 100	4	1/4 NPT	on request
0 ... 160	5	Output signal	Substitute
0 ... 250	6	1 x PNP	1
0 ... 400	7	2 x PNP	2
0 ... 630	8	1 x PNP/1 x analogue	4
		4 ... 20 mA	

Accessories

<p>Pressure port reducing nipple</p> <p>see below</p> <p>0574767 (brass) 0550083 (stainless steel)</p>	<p>Surge damper nipple</p> <p>see below</p> <p>0574773 (brass) 0553258 (stainless steel)</p>
---	---


<p>Connector M12 x 1</p> <p>4- or 5-pin, 90°</p> <p>0523058 (2 m cable, 4-core) 0523053 (5 m cable, 4-core) 0250081 (5 m cable, 5-core, on PE-requirement *1)</p>	<p>4-pin, 90°</p> <p>0523056 (without cable)</p>	<p>4-pin, straight</p> <p>0523057 (2 m cable, 4-core) 0523052 (5 m cable, 4-core)</p>	<p>4-pin, straight</p> <p>0523055 (without cable)</p>
--	--	---	---

*1) Cable with screening

Electrical connection M12 x 1

	PIN-No.	Signal	Cable
	1	+ UB	brown
	2	Out 2 (PNP) / analogue 4 ... 20 mA	white
	3	0 Volt	blue
	4	Out 1 (PNP)	black
	5	PE (Protected Earth)	grey

Dimensions G1/4 and Flange Versions




Dimensions in mm
Projection/First angle




Pressure port reducing nipple

Model: 0574767 (brass)
0550083 (stainless steel)



Surge damper nipple

Model: 0574773 (brass)
0553258 (stainless steel)



Warning

These products are intended for use in industrial compressed air and fluid systems only. Do not use these products where pressures and temperatures can exceed those listed under »**Technical features/data**«. Before using these products with fluids other than those specified, for non-industrial applications, life-support systems, or other applications not within published specifications, consult IMI Precision Engineering, Norgren GmbH.

Through misuse, age, or malfunction, components used in fluid power systems can fail in various modes. The system designer is warned to consider the failure modes of all component parts used in fluid power systems and to provide adequate safeguards to prevent personal injury or damage to equipment in the event of such failure.

System designers must provide a warning to end users in the system instructional manual if protection against a failure mode cannot be adequately provided.

System designers and end users are cautioned to review specific warnings found in instruction sheets packed and shipped with these products.